



ARIAS COMERCIAL
IMPORTADORES Y DISTRIBUIDORES
Al servicio de la industria y ferretería



**RUEDA INDUSTRIA
ALIMENTICIA**

Heredia, San joaquin de flores



2265-6620
8679-6520
arcosacr@yahoo.com



VELOX



CARATTERISTICHE TECNICHE

- Temperatura di utilizzo: da -25°C a + 80°C
- Velocità massima di lavoro: 4 Km/h
- Impiego orientativo: Carrelli a traslazione manuale per carichi medi.
- Buona resistenza all'abrasione, a numerosi prodotti petroliferi ed agenti chimici.
- Temono il contatto con acidi forti.

STRUTTURA

- Ruota monolitica in poliammide 6 di colore neutro.
- Corpo greccato per diametri 80, 100, 125 e 150, liscio per i diametri 175 e 200.

TECHNICAL SPECIFICATIONS

- Ambient temperatures: between -25 and +80°C.
- Maximum speed: 4 Km/h.
- Applications: Hand trolleys for medium loads.
- Good resistance to abrasion, to several petroleum byproducts and chemical agents.
- Contact with strong acids should be avoided.

STRUCTURE

- One piece wheel made of Polyamide 6, neutral colour.
- Wheels ø80, 100, 125 and ø150: center with moulded spokes. Wheels ø175 and 200: flat disk.

		Mozzo con foro passante. Hub with plain bearing	Mozzo con cuscinetto a rullini. Hub with roller bearing	Mozzo con cuscinetto a rullini in acciaio INOX . Hub with STAINLESS STEEL roller bearings

mm	Type	mm	mm	Type	mm	mm	Type	mm	mm	mm	daN
80	NVB	12	39	NVR	12	39	NVR/4	12	39	30	100
100	NVB	12	39	NVR	12	39	NVR/4	12	39	30	130
125	NVB	15	44	NVR	15	44	NVR/4	15	44	39	200
150	NVB	20	45	NVR	20	45	NVR/4	20	45	40	250
175	NVB	20	58	NVR	20	59	NVR/4	20	59	45	300
200	NVB	20	58	NVR	20	59	NVR/4	20	59	50	380



ARIAS COMERCIAL
 IMPORTADORES Y DISTRIBUIDORES
 Al servicio de la industria y ferretería
arcosacr@yahoo.com



2265-6620
 8679-6520

Heredia, San Joaquín.

VELOX - E line



NVPB



NVPR



Supporto rotante a piastra in lamiera stampata e zincata con gruppo rotante realizzato con doppia corona di sfere. Dado autobloccante al mozzo.

Zinc plated, pressed steel, swivel housing, plate fitting, with double ball race. Axle assembled with a self locking nut.



mm	Type	Type	daN	mm	mm	mm x mm	mm x mm	mm	mm x mm	mm	
80	NVPB	NVPR	100	108	32	100x80	80x60	9	40x8	.../2	116
100	NVPB	NVPR	130	127	33	100x80	80x60	9	40x8	.../2	116
125 L	NVPB	NVPR	180	155	39	100x80	80x60	9	44x8	.../2	124
125	NVPB	NVPR	200	159	46	117x85	80x60	9	44x8	.../2	130
150	NVPB	NVPR	220	186	47	133x106	105x80	11	48x10	.../2	144
175	NVPB	NVPR	300	216	55	132x110	105x80	11	60x12	.../2	156
200	NVPB	NVPR	300	240	56	132x110	105x80	11	60x12	.../2	158

VELOX - X line



NVPBX



NVPRX



Supporto rotante tipo "X LINE" a piastra in lamiera stampata e zincata con gruppo rotante realizzato con doppia corona di sfere. Dado autobloccante al mozzo.

Zinc plated, pressed steel, "X LINE" swivel housing, plate fitting, with double ball race. Axle assembled with a self locking nut.



mm	Type	Type	daN	mm	mm	mm x mm	mm x mm	mm	mm x mm	mm	
80	NVPBX	NVPRX	100	108	32	95x80	80x60	9	40x8	.../2	110
100	NVPBX	NVPRX	130	127	32	95x80	80x60	9	40x8	.../2	110
125 L	NVPBX	NVPRX	130	155	32	95x80	80x60	9	44x8	.../2	113
150 LL	NVPBX	NVPRX	150	184	35	100x80	80x60	9	44x8	.../2	115
150 P	NVPBX	NVPRX	250	192	52	129x106	105x80	11	60x12	.../2	150
175	NVPBX	NVPRX	270	228	48	129x106	105x80	11	60x12	.../2	150
200	NVPBX	NVPRX	270	240	48	129x106	105x80	11	60x12	.../2	150



ARIAS COMERCIAL
 IMPORTADORES Y DISTRIBUIDORES
 Al servicio de la industria y ferretería
arcosacr@yahoo.com



2265-6620
 8679-6520

Heredia, San Joaquín.



VELOX - E line



NVOB



NVOR



Supporto rotante a foro passante in lamiera stampata e zincata con gruppo rotante realizzato con doppia corona di sfere. Dado autobloccante al mozzo.

Zinc plated, pressed steel, swivel housing. Bolt hole fitting, with double ball race. Axle assembled with a self locking nut.



mm	Type	Type	daN	mm	mm	mm	mm	mm x mm	mm	
80	NVOB	NVOR	100	108	32	12	65	40x8	.../2	116
100	NVOB	NVOR	120	127	33	12	65	40x8	.../2	116
125L	NVOB	NVOR	120	155	39	12	65	44x8	.../2	124
125	NVOB	NVOR	120	159	46	12	73	44x8	.../2	130
150	NVOB	NVOR	120	186	47	12	80	48x10	.../2	144
175	NVOB	NVOR	150	216	55	12	93	60x12	.../2	156
200	NVOB	NVOR	150	240	56	12	93	60x12	.../2	158

VELOX - X line



NVOBX



NVORX



Supporto rotante tipo "X LINE" a foro passante in lamiera stampata e zincata con gruppo rotante realizzato con doppia corona di sfere. Dado autobloccante al mozzo.

Zinc plated, pressed steel, "X LINE" swivel housing Bolt hole fitting, with double ball race. Axle assembled with a self locking nut.



mm	Type	Type	daN	mm	mm	mm	mm	mm x mm	mm	
80	NVOBX	NVORX	100	108	32	12	64	40x8	.../2	110
100	NVOBX	NVORX	130	127	32	12	64	40x8	.../2	110
125L	NVOBX	NVORX	130	155	32	12	64	44x8	.../2	113
150LL	NVOBX	NVORX	140	184	35	12	65	44x8	.../2	115
150P	NVOBX	NVORX	250	192	52	16	95	60x12	.../2	150
175	NVOBX	NVORX	270	228	48	16	95	60x12	.../2	150
200	NVOBX	NVORX	270	240	48	16	95	60x12	.../2	150



ARIAS COMERCIAL
 IMPORTADORES Y DISTRIBUIDORES
 Al servicio de la industria y ferretería
arcosacr@yahoo.com



2265-6620
 8679-6520

Heredia, San Joaquín.

VELOX - E line



NVCB



NVCR



Supporto rotante a codolo in lamiera stampata e zincata con gruppo rotante realizzato con doppia corona di sfere. Dado autobloccante al mozzo.

Zinc plated, pressed steel, swivel housing
Solid stem fitting, with double ball race.
Axle assembled with a self locking nut.



mm	Type	Type	daN	mm	mm	mm	mm	mm	mm x mm	mm	
80	NVCB	NVCR	100	108	32	20	45	65	40x8	.../2	116
100	NVCB	NVCR	120	127	33	20	45	65	40x8	.../2	116
125	NVCB	NVCR	150	159	46	22	55	73	44x8	.../2	130
150	NVCB	NVCR	150	186	47	22	55	80	48x10	.../2	144
175	NVCB	NVCR	170	216	55	26	65	93	60x12	.../2	156
200	NVCB	NVCR	200	240	56	26	65	93	60x12	.../2	158



ARIAS COMERCIAL
 IMPORTADORES Y DISTRIBUIDORES
 Al servicio de la industria y ferretería
arcosacr@yahoo.com



2265-6620
 8679-6520
 Heredia, San Joaquín.

VELOX - E line / X line



NVFB / NVFBX NVFR / NVFRX



Supporto fisso in lamiera stampata e zincata.
Dado autobloccante al mozzo.

Zinc plated pressed steel fixed housing.
Axle assembled with a self locking nut.



mm	Type	Type	daN	mm	mm x mm	mm x mm	mm	mm
80	NVFB	NVFR	100	108	100 x 84	80 x 60	9	40x8
100	NVFB	NVFR	130	127	100 x 84	80 x 60	9	40x8
125L	NVFB	NVFR	180	155	100 x 84	80 x 60	9	44x8
125	NVFB	NVFR	200	159	116 x 84	80 x 60	9	44x8
150LL	NVFBX	NVFRX	140	184	100 x 84	80 x 60	9	44x8
150	NVFB	NVFR	220	186	135 x 110	105 x 80	11	48x10
150P	NVFBX	NVFRX	250	192	135 x 110	105 x 80	11	60x12
175	NVFB	NVFR	300	216	135 x 110	105 x 80	11	60x12
175	NVFBX	NVFRX	270	228	135 x 110	105 x 80	11	60x12
200	NVFB	NVFR	300	240	135 x 110	105 x 80	11	60x12



ARIAS COMERCIAL
 IMPORTADORES Y DISTRIBUIDORES
 Al servicio de la industria y ferretería
arcosacr@yahoo.com



2265-6620
 8679-6520
 Heredia, San Joaquín.



CARATTERISTICHE TECNICHE

- Temperatura di utilizzo: da -25°C a +80°C
- Velocità massima di lavoro: 4 Km/h
- Impiego orientativo: Carrelli a traslazione manuale per carichi gravosi.
- Buona resistenza all'abrasione, a numerosi prodotti petroliferi ed agenti chimici.
- Temono il contatto con acidi forti.

STRUTTURA


- Ruota monolitica in poliammide 6 di colore neutro.

TECHNICAL SPECIFICATIONS

- Ambient temperatures: between -25 and +80°C.
- Maximum speed: 4 Km/h.
- Applications: Hand trolleys for heavy loads.
- Good resistance to abrasion, to several petroleum byproducts and chemical agents.
- Contact with strong acids should be avoided.

STRUCTURE

- One piece wheel made of Polyamide 6, neutral colour.




NPB



Mozzo con foro passante.
Hub with plain bearing

NPC



Mozzo con cuscinetti a sfere.
Hub with ball bearing

NPC/R



Mozzo rinforzato con cuscinetti a sfere.
Reinforced hub with ball bearings



mm	Type	mm	mm	daN	Type	mm	mm	daN	Type	mm	mm	daN
100x35	NPB	20	44	370	NPC	15	40	370	-	-	-	-
100Rx40	-	-	-	-	-	-	-	-	NPC/R	15	44	650
125x35	NPB	20	44	380	NPC	15	40	380	-	-	-	-
125Px45	NPB	20	58	600	NPC	20	58	600	-	-	-	-
125Rx45	-	-	-	-	-	-	-	-	NPC/R	20	58	750
150x40	NPB	20	49	380	NPC	20	49	380	-	-	-	-
150Px45	NPB	20	58	700	NPC	20	58	700	-	-	-	-
150Rx45	-	-	-	-	-	-	-	-	NPC/R	20	58	1.000
200x50	NPB	20	58	800	NPC	20	58	800	-	-	-	-
200Rx50	-	-	-	-	-	-	-	-	NPC/R	20	59	1.000



ARIAS COMERCIAL
IMPORTADORES Y DISTRIBUIDORES
Al servicio de la industria y ferretería
arcosacr@yahoo.com



2265-6620
8679-6520
Heredia, San Joaquín.

NP - INOX - STAINLESS STEEL



NPBP/4



Supporto rotante a piastra.

Swivel housing, plate fitting.



mm	Type	Type	daN	mm	mm	mm x mm	mm x mm	mm	Type	mm
100 x 35	NPBP/4	-	300	128	42	100x84	80x60	9	.../2F	114
125 x 35	NPBP/4	-	380	154	53	100x84	80x60	9	.../2F	128
125P x 45	NPBP/4	-	600	164	61	132x110	105x80	12	.../2F	158
150P x 45	NPBP/4	-	600	195	62	132x110	105x80	12	.../2F	157
200 x 50	NPBP/4	-	600	242	61	132x110	105x80	12	.../2F	158
200R x 50	-	NPCP/4	1.000	246	61	132x110	105x80	12	.../2F	158



Supporto fisso a piastra.

Fixed housing, plate fitting.

NPBF/4



mm	Type	Type	daN	mm	mm x mm	mm x mm	mm
100 x 35	NPBF/4	-	370	128	100x88	80x60	9
125 x 35	NPBF/4	-	380	157	100x88	80x60	9
125P x 45	NPBF/4	-	600	164	134x114	105x80	12
150P x 45	NPBF/4	-	600	195	134x114	105x80	12
200 x 50	NPBF/4	-	600	242	134x114	105x80	12
200R x 50	-	NPCF/4	1.000	246	134x114	105x80	12



ARIAS COMERCIAL
 IMPORTADORES Y DISTRIBUIDORES
 Al servicio de la industria y ferretería
arcosacr@yahoo.com



2265-6620
 8679-6520

Heredia, San Joaquín.